



FIVE HEAD COLD PRESS OIL MACHINE

Height: 2.3m

Length: 1.5m

Width: 1m

Weight : 750 KG (1550lbs)

Capacity: 0.75-1 Ton/day (depending on nozzle used, seed density and moisture)

Motor: 5.5kW standard with 2.2kW and 7.5kW options, independent motor option available in a variety of voltages (please specify)

Typical oil removal: 85-90% (depending on nozzle, moisture and seed condition)

Materials used:

1.4121 SS, 1.4125 SS, 1.2379 SS and 51420 CHROME NICKEL

We source our materials from a German-Turkish joint venture which is known worldwide for top quality products. See www.birlesikmetal.com.tr

We perform a heating and hardening process that subjects components to 1030-1050C temperatures (depending on material) and reheated after cooling to 150 C. Final processing includes coating with nickel phosphate to increase durability.

The standard 5 head press includes an integrated feed bunk, digital speed and heat control and stand to enable ease of operation, optimization and repeatability. Our systems are expandable to ensure customers achieve projected scale up results.

Nebraska Screw Press is the authorized North American dealer for this equipment from www.tokultarim.com and provides a 20 year warranty on drive systems. Top quality replacement parts for your Tokul or Komet presses are stocked in our Nebraska facility for fast delivery.

Contact us for references, pricing and further information regarding your next project.